

## **New Battery Installation Instructions For Time Machine:**

1. Turn off Time Machine.
2. Remove four countersunk screws from sides of enclosure.
3. Separate enclosure halves by lifting up the top half on the left (printer) side and then slide it to the right. This is done by removing the printer cover and pressing down on the printer while pulling up on the enclosure top, then slide the enclosure top to the right so that it clears the connectors on the right hand side.
4. Remove the printed circuit board by removing the four screws that hold it in place.
5. The battery is now accessible. Remove the two battery cover screws along with the battery cover and the foam pad on top of the battery.
6. If battery wires are not color coded (red (+) & black (-)), then mark the wires with “+” and “-” using masking tape. Look at the battery terminal markings (+ or -) to determine how to mark the wires.
7. Unsolder the wires from the old battery.
8. Re-solder the battery wires to the new battery being careful to solder the red (or “+” marked) wire to the “+” terminal and the black (or “-” marked) wire to the “-” terminal.
9. Turn on the Time Machine to verify that it works properly. Turn Time Machine off.
10. Re-assemble the Time Machine: Install the battery cover (make sure to place the foam pad on the battery so it doesn't rattle), install the printed circuit board and install the enclosure top. Perform re-assembly in the reverse order from which it was disassembled. Note: Take care so that the “charge LED” is properly inserted back into it's hole. You may have to bend it down to ensure that it is positioned correctly.